

Printing Materials

Guide Information

F.P.E. S.R.L.

Lillo del Duca 20, BRESSO MI 20091 IT

printed stock dsq: TTC.41.(XXXX)-(YY), TTC.41G.(XXXX)-(YY)

Pressure-sensitive systems

Suitable for additional printing with one or more of the following inks (in the black color unless otherwise indicated):

Additional Printing Note: Additional Printing inks are suitable for indoor and outdoor use flood coated areas, unless otherwise specified

Thermal transfer ribbon

Armor AXR 7+

Dainippon R300, TR5080

Ricoh B110A

Zebra Technologies Corp. 5095

<u>Application Surface</u>	<u>Max Temp</u> (°C)	<u>Min Temp</u> (°C)	<u>Indoor</u> <u>Use</u>	<u>Outdoor</u> <u>Use</u>	<u>Additional</u> <u>Conditions</u>
Stainless steel	80	-29	Yes	Yes	-

(XXXX) - To be replaced by four numbers indicating: size of the label, labels per row, per roll and size of printable area per label.

(YY) - To be replaced by 2 or 3 letters indicating customers' specifics, which do not impact the UL Safety critical properties.

Report Date: 2021-05-25

Last Revised: 2021-05-26

© 2021 UL LLC

