



## Tabella dei formati standard serie TTC.41 e TTC.41G in PVC per l'applicatore Wicon



MH 64678

Area di stampa bianca 

Altezza in mm	Base in mm	Area di stampa (altezza)	Area di stampa (base)	Larghezza bobina in mm	Etichette per riga	Etichette per bobina	Adatte per Ø cavi mm	Codice
19,10	12,70	6,40	12,70	17,70	1	7.000	2.0 - 4.0	TTC.41.0001-WI
19,10	25,40	6,40	25,40	30,40	1	7.000	2.0 - 4.0	TTC.41.0002-WI
25,40	25,40	9,50	25,40	30,40	1	5.000	3.0 - 5.0	TTC.41.0003-WI
38,10	12,70	12,70	12,70	17,70	1	3.500	4.0 - 8.0	TTC.41.0004-WI
38,10	19,10	12,70	19,10	24,10	1	3.500	4.0 - 8.0	TTC.41.0005-WI
38,10	25,40	12,70	25,40	30,40	1	3.500	4.0 - 8.0	TTC.41.0006-WI
38,10	50,80	12,70	50,80	55,80	1	3.500	4.0 - 8.0	TTC.41.0007-WI
50,00	23,00	20,00	23,00	28,00	1	2.500	5.0 - 12.0	TTC.41.0008-WI
63,50	25,40	19,10	25,40	30,40	1	2.000	6.0 - 14.0	TTC.41.0009-WI
63,50	38,10	19,10	38,10	43,10	1	2.000	6.0 - 14.0	TTC.41.0010-WI
70,00	25,40	19,10	25,40	30,40	1	2.000	6.0 - 16.0	TTC.41.0011-WI
70,00	50,80	19,10	50,80	55,80	1	2.000	6.0 - 16.0	TTC.41.0012-WI

Area di stampa gialla 

Altezza in mm	Base in mm	Area di stampa (altezza)	Area di stampa (base)	Larghezza bobina in mm	Etichette per riga	Etichette per bobina	Adatte per Ø cavi mm	Codice
19,10	12,70	6,40	12,70	17,70	1	7.000	2.0 - 4.0	TTC.41G.0001-WI
19,10	25,40	6,40	25,40	30,40	1	7.000	2.0 - 4.0	TTC.41G.0002-WI
25,40	25,40	9,50	25,40	30,40	1	5.000	3.0 - 5.0	TTC.41G.0003-WI
38,10	12,70	12,70	12,70	17,70	1	3.500	4.0 - 8.0	TTC.41G.0004-WI
38,10	19,10	12,70	19,10	24,10	1	3.500	4.0 - 8.0	TTC.41G.0005-WI
38,10	25,40	12,70	25,40	30,40	1	3.500	4.0 - 8.0	TTC.41G.0006-WI
38,10	50,80	12,70	50,80	55,80	1	3.500	4.0 - 8.0	TTC.41G.0007-WI
50,00	23,00	20,00	23,00	28,00	1	2.500	5.0 - 12.0	TTC.41G.0008-WI
63,50	25,40	19,10	25,40	30,40	1	2.000	6.0 - 14.0	TTC.41G.0009-WI
63,50	38,10	19,10	38,10	43,10	1	2.000	6.0 - 14.0	TTC.41G.0010-WI
70,00	25,40	19,10	25,40	30,40	1	2.000	6.0 - 16.0	TTC.41G.0011-WI
70,00	50,80	19,10	50,80	55,80	1	2.000	6.0 - 16.0	TTC.41G.0012-WI

Ribbon in resina suggerito : R300 certificato UL